



## HEAT-CONDUCTING PIPES - SP

mail@ waermeleitrohre.de  
www.waermeleitrohre.de

- WÄRMELEITROHRE SP • CALODUCS SP • CONDOTTA TERMICA SP •
- CARTOUCHE THERMOCONDUCTRICE SP • TEPELNÉ TRUBICE SP •
- VARMELEIDERØR SP • WARMTEPIJP SP •

Type SP	Operating temperatures:
	<p><b>20° to 320°C</b> with reference to the surface areas of the heat-conducting pipes SP</p> <p><b>20° to 500°C</b> with reference to the surface areas of the casting tooling</p>

Standard sizes	Lengths L ±1								
	50	63	80	100	125	160	200	250	M
Ød 3 <sup>+0.05</sup> <sub>-0.10</sub>									
4 <sup>+0.05</sup> <sub>-0.10</sub>									2.5
5 <sup>+0.05</sup> <sub>-0.10</sub>									3
6 <sup>+0.05</sup> <sub>-0.10</sub>									3
8 <sup>+0.05</sup> <sub>-0.10</sub>									4
10 <sup>+0.05</sup> <sub>-0.10</sub>									5
12 <sup>+0.05</sup> <sub>-0.15</sub>									6
16 <sup>+0.05</sup> <sub>-0.20</sub>									8

Angaben in mm

- Delivery times: standard lengths ex stock. Offered subject to prior sale. Special lengths on request
- All goods supplied in accordance with our General Conditions of Business.
- We reserve the right to make technical and commercial changes.